

INTERNAL KEYLESS LOCKING DEVICES



- Zero backlash transmissions
- High torques transmissible
- Designs for high bending moments
- Self centering designs
- Small radial-dimensions solutions
- MIDAS modular systems
- Zinc plating
- Nickel plating

SHRINK DISCS



- Standard 3 pieces shrink discs
- 2 pieces shrink discs for high speed applications
- Hollow shafts from 14 mm up to 800 mm
- Transmissible torques from 20 Ft-lb up to 1,435,000 Ft-lb
- Black phosphatation
- Zinc plating
- Nickel plating
- Multi-layer painting, over size 200mm

TORQUE LIMITERS



STANDARD VERSIONS

- Single-position re-engagement
- Multi-position re-engagement
- Load holding version
- Full disengagement version

BACKLASH FREE

- Multi-position re-engagement
- Single-position re-engagement

FRICTION SERIES

- Torque limiter for parallel shafts
- Torque limiter+roller chain coupling

COUPLINGS



DISC COUPLINGS

- Zero backlash transmission
- High torsional stiffness
- Transmissible torque: 11 ft-lb up to 95,885 ft-lb
- Shafts from 8 mm up to 260 m

BELOW COUPLINGS

- Zero backlash transmission
- High torsional stiffness
- Low inertia for high speed applications



sales@rotafree.com



630-395-9789



www.rotafree.com



2846 Hitchcock ave.
Downers Grove
(IL) 60515